

Kanlux TYBIA LED

PLAFONIERA LED ► CEILING-MOUNTED LED LIGHT FITTING



TYBIA LED 38W-NW; NW-SE



Kanlux TYBIA LED to oprawa oświetlenia ogólnego, w której zastosowano diody SMD. Montaż oprawy TYBIA LED w korytarzach, klatkach schodowych, pokojach socjalnych czy gospodarczych, gwarantuje znaczne oszczędności nie tylko związane z poborem energii ale także jej długoterminową, bezobsługową eksploatacją.

Materiał obudowy: stop aluminium
Materiał klosza: PMMA


Kanlux TYBIA LED is a general lighting luminaire using SMD diodes. When mounted in corridors, staircases, social or utility rooms, TYBIA LED allows for significant savings related to both reduced energy consumption and the long-term maintenance-free operation.

Enclosure material: aluminum alloy
Lampshade material: PMMA



TYBIA LED 38W-NW	24640	5905339246400	38	3500	4000	szary / biały grey / white
TYBIA LED 38W-NW-SE	24641	5905339246417	38	3500	4000	szary / biały grey / white mikrofalowy microwave

[V]	[Hz]	[°]	[h]	[lm]	[K]	[Ra]	[SMD]	[Sensor]
220-240 AC	50/60	110	≥20000	30000	≤6xMaxdam	≥80	SMD	SENSOR
IP 20	House icon	5+25	Mounting icon	1-2,5	0,5m	CE	ERAC	Kanlux logo



TYBIA LED 38W; 38W SE

Kanlux PORTOS LED

PLAFONIERA LED ► CEILING-MOUNTED LED LIGHT FITTING



PORTOS LED




Kanlux PORTOS to wytrzymała i odporna na działanie czynników zewnętrznych oprawa LED. Może być stosowana zarówno w pomieszczeniach, jak i na zewnątrz, bez obaw, że wilgoć i pył zmniejszą jej wydajność pracy.

Materiał obudowy: tworzywo sztuczne
Materiał klosza: tworzywo sztuczne


The Kanlux PORTOS is a LED fixture which is durable and resistant to exposure to external factors. It can be used both indoors and outdoors, without the risk of moisture and dust reducing its efficiency.

Enclosure material: plastic
Lampshade material: plastic



PORTOS LED	29070	5905339290700	5	500	4000	biały white
------------	--------------	---------------	---	-----	------	---------------

[V]	[Hz]	[°]	[h]	[lm]	[K]	[Ra]	[SMD]	[Sensor]
220-240 AC	50/60	120	≥10000	30000	4000	≤6xMaxdam	≥80	SMD
IP 54	House icon	-10+35	Mounting icon	0,5+1,5	0,5m	CE	ERAC	Kanlux logo



PORTOS LED