

Kanlux

HB PRO LED HI

OPRAWA LED HIGH BAY ► HIGH-BAY LED LIGHT FITTING

NEW




HB PRO LED HI 100W



HB PRO LED HI 150W




HB PRO LED HI 200W



HB PRO LED HI 100W-NW	27155	5905339271556	100	14000	4000	czarny black
HB PRO LED HI 150W-NW	27156	5905339271563	150	21750	4000	czarny black
HB PRO LED HI 200W-NW	27157	5905339271570	200	29250	4000	czarny black

[V]	[Hz]	[°]	[h]	[lm]	[°C]	[°C]
220-240 AC	50	90	≥15000	30000	4000	≤6x MacAdam
Ra ≥80	SMD	IP 65	-20+40			
1m	CE	EAC				



5+
WARRANTY
5 years

IP
65

HI
GH
efficacy

Kanlux HB PRO HI to oprawy typu „High Bay”. Oprócz energooszczędności, jaką gwarantuje zastosowana w nich technologia LED, cechuje je też niezwykle duża trwałość i wysoki stopień szczelności IP65. Idealnie sprawdzą się w wysokich halach magazynowych, produkcyjnych czy sklepowych. Dodatkowym atutem tych opraw jest zintegrowana puszka przyłączeniowa, która usprawnia montaż. Kanlux HB PRO HI to również duże strumienie świetlne i wysoka skuteczność na poziomie niemal 150 lumenów z Wata.

5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej

Materiał obudowy: stop aluminium


Materiał szyby ochronnej: tworzywo sztuczne

Kanlux HB PRO LED are “High Bay” luminaires. Apart from the energy efficiency of the applied LED technology, they are characterised by extremely high durability and tightness of IP65. It is an excellent choice for high storage, production or shop halls. An additional advantage of these luminaires is an integrated junction box which makes the installation easier. Kanlux HB PRO HI also offers both a high luminous flux and a high luminous efficiency of 150 lm/W.


5 years Warranty under the terms of the warranty statement, available on our website

Enclosure material: aluminum alloy


Protective glass material: plastic



HB PRO LED HI 100W



HB PRO LED HI 150W



HB PRO LED HI 200W